

In the Claims:

Claims 1 to 6 (canceled).

- 1 **7.** (new) A filtration apparatus comprising:
- 2 a housing head having an inlet and an outlet;
- 3 a housing bowl detachably attached to said housing
- 4 head and surrounding a cartridge filter to define a channel
- 5 wall; and
- 6 a releasable clamping device that exerts a force to
- 7 press said housing head and said housing bowl against each
- 8 other to clamp said housing head and said housing bowl
- 9 together, wherein:
- 10 said housing head has a ring-shaped first sealing
- 11 portion that faces said housing bowl;
- 12 said housing bowl has a ring-shaped second sealing
- 13 portion that abuts directly against said first sealing
- 14 portion when said clamping device exerts said force to
- 15 press said housing head and said housing bowl against each
- 16 other;
- 17 one of said first and second sealing portions is a
- 18 protrusion and another of said first and second sealing
- 19 portions is a recess;
- 20 with respect to an axial-section along a cylindrical
- 21 axis line of said housing head and said housing bowl, said
- 22 protrusion has a radially inner arcuate curved protrusion
- 23 surface and a radially outer arcuate curved protrusion
- 24 surface;

4277/WFF:ar

- 4 -

25 said recess is bounded by a radially inner recess wall
26 portion and a radially outer recess wall portion; and

27 said radially inner arcuate curved protrusion surface
28 presses against said radially inner recess wall portion to
29 form a first inner circular seal, and said radially outer
30 arcuate curved protrusion surface presses against said
31 radially outer recess wall portion to form a second outer
32 circular seal.

1 8. (new) The filtration apparatus according to claim 7,
2 wherein said radially inner and radially outer arcuate
3 curved protrusion surfaces are portions of an overall
4 semi-circular curved sectional shape of said protrusion
5 with respect to said axial section.

1 9. (new) The filtration apparatus according to claim 7,
2 wherein said radially inner recess wall portion and said
3 radially outer recess wall portion each have an arcuate
4 curved shape with respect to said axial section.

1 10. (new) The filtration apparatus according to claim 9,
2 wherein said radially inner and radially outer recess wall
3 portions are portions of an overall semi-circular curved
4 sectional shape of said recess with respect to said axial
5 section.

1 11. (new) The filtration apparatus according to claim 7,
2 excluding any O-ring between said housing head and said
3 housing bowl.

1 12. (new) The filtration apparatus according to claim 7,
2 wherein, when said recess and said protrusion are pressed
3 against each other, said recess is increased in width
4 elastically and has resilience allowing said recess to
5 cooperate with said protrusion to form said seals.

1 13. (new) The filtration apparatus according to claim 7,
2 wherein said housing head, said cartridge filter and said
3 housing bowl are all formed of a fluororesin.

[RESPONSE CONTINUES ON NEXT PAGE]

4277/WFF:ar

- 6 -